

FLOW METERS FOR SPECIAL APPLICATIONS



SONOELIS SE401x.xRP and SONOELIS SE402x.xRP

- for application in different fields of industries with request of transducers changing during operation
- flow–rate, volume measurement of conductive and non–conductive clean liquids in dimensions DN400 to DN1200 (12" to 48")
- maximum pressure 10 bar (150psi) related to diameter
- replaceable probes for flooded pipes
- maximum temperature of measured medium 100°C (212°F)
- measurement accuracy according to EN ISO 4064–1 (OIML R 49) class 2
- communication RS 485, electrical outputs



SONOELIS SE4015.xT

- for application in energy for measurement of feeding water to boilers
- flow–rate, volume measurement of water for high pressure in piping
- dimensions DN80 to DN200 (3" to 8")
- maximum pressure 240 bar (3500psi) related to diameter
- one beam version
- maximum temperature of measured medium 150°C (302°F)
- measurement accuracy ±1% for velocity of liquid $v > 1\text{ m/s}$
- communication RS 485, electrical outputs



SONOELIS SE804x.x and SONOELIS SE806x.x

- for application in water, energy, light and haevy industry
- flow–rate, volume measurement of water of big dimensions with direct assembly
- one and dual beam version
- dimensions DN200 to DN1200 (8" to 48")
- maximum pressure 40 bar (600psi) related to diameter
- maximum temperature of measured medium 150°C (302°F)
- measurement accuracy ±2% one beam, ±1% dual beam
- communication RS 485, electrical outputs



FLONET FS10xx

- for application in water, energy, light and haevy industry
- flow–rate and volume measurement of conductive abrasive liquids and mixtures
- dimensions DN100 to DN200 (4" to 8") – wafer
- dimensions DN250 to DN450 (10" to 18")– flanges
- maximum pressure 16 bar (300psi) related to diameter
- maximum temperature of measured medium 150°C (302°F)
- accuracy of measurement ±1%
- communication Hart, electrical outputs

HEAT/COLD METERS

MID Certified



ELISTHERM ET3020.x3

- measurement of absolute heat and cold energy delivered or consumed in closed heating/cooling systems
- dimensions DN32 to DN300 (1 1/4" to 12")
- maximum temperature of measured medium 150°C (302°F)
- measurement accuracy according to EN 1434 (OIML R75) class 2
- communication M–Bus, electrical outputs

MID Certified



ELISTHERM ET3020.x7

- measurement of absolute heat and cold energy delivered or consumed in closed heating/cooling systems
- dimensions DN200 to DN1200 (8" to 48")
- maximum temperature of measured medium 150°C (302°F)
- measurement accuracy according to EN 1434 (OIML R75) class 2
- communication M–bus, electrical outputs



ELISTHERM ET3010.0

- measurement of absolute heat and cold energy delivered or consumed in closed heating/cooling systems
- dimensions DN20 to DN500 (3/4" to 20")
- maximum temperature of measured medium 150°C (302°F)
- measurement accuracy according to EN 1434 (OIML R75) class 2
- communication M–Bus, electrical outputs



ELIS PLZEŇ a. s.
LUČNÍ 425/15
301 00 PLZEŇ
CZECH REPUBLIC

PHONE: +420 377 517 711
FAX: +420 377 517 722
e-mail: sales@elis.cz
http://www.elis.cz



ELIS PLZEŇ a. s.

MEASUREMENT OF FLOW AND ENERGY

MEASUREMENT OF FLOW AND ENERGY

ELECTROMAGNETIC FLOW METERS



FLONET FN20xx.1

- for application mainly in water industry
- flow-rate and volume measurement of conductive liquids
- dimensions DN6 to DN1200 (1/4" to 48")
- maximum pressure 40 bar (600psi) related to diameter
- maximum temperature of measured medium 150°C (302°F)
- measurement accuracy according to EN ISO 4064-1 (OIML R49) class 2
- communication RS 485, electrical outputs



FLONET FN50xx

- for application mainly in water industry
- flow-rate and volume measurement of conductive liquids for heat and cold measurement (blind version)
- dimensions DN20 to DN500 (3/4" to 20")
- maximum pressure 40 bar (600psi) related to diameter
- maximum temperature of measured medium 150°C (302°F)
- measurement accuracy according to EN1434 (OIML R 75), class 2
- pulse electrical output



FLONET FH30xx

- for application mainly in water industry
- flow-rate and volume measurement of conductive liquids
- dimensions DN15 to DN1200 (3/4" to 48")
- maximum pressure 40bar (600psi) related to diameter
- maximum temperature of measured medium 150°C (302°F)
- measurement accuracy according to EN ISO 4064-1 (OIML R 49) class 2
- communication MODBUS RTU, electrical outputs



FLONEX FXx11x

- for application in hazardous environment
- flow-rate and volume measurement of conductive liquids
- dimensions DN15 to DN300 (1/2" to 12")
- maximum pressure 40bar (150psi) related to diameter
- ambient temperature max. range -35°C to +60°C (-31°F to 140°F) depending on temperature class: T3 to T6
- measurement accuracy according to EN ISO 4064-1 (OIML R 49) class 2
- communication MODBUS RTU, electrical outputs
- ATEX / IEC approval II 2G Ex db eb ib [ib] IIB T6...T3 Gb
II 2D Ex tb IIIC T80°C...T155°C Db

BATTERY POWERED ULTRASONIC FLOW METERS



FLOMIC FL503x and FLOMIC FL505x

- for application in water and light industry
- flow-rate, volume and pressure measurement of liquids
- one and dual beam version, dimensions DN32 to DN300 (1 1/4" to 12")
- water pressure class MAP 16 or MAP 40 (related to diameter)
- flow-rate sampling period 1s
- storage of measured dates
- measurement accuracy according to EN ISO 4064-1 (OIML R 49) class 2
- communication USB, RS 232, GSM, electrical outputs
- compact or remote version, protection class IP68



FLOMIC FL3085

- for application in water industry
- flow-rate and volume measurement in water supply networks of big dimensions
- one beam version, DN200 to DN1200 (8" to 48")
- maximum pressure 25bar (600psi) related to diameter
- maximum temperature of measured water 150°C (302°F)
- measurement accuracy according to EN ISO 4064-1 (OIML R 49) class 2
- storage of measured dates
- communication GSM, optical interface, electrical outputs



FLOMIC FL3005

- for application in water industry
- flow-rate and volume measurement in water supply networks of big dimensions with direct assembly
- one beam version, DN200 to DN2000 (8" to 80")
- maximum pressure 40bar (600psi)
- maximum temperature of measured water 150°C (302°F)
- accuracy of measurement ±2% by theoretical calibration
- storage of measured dates
- communication GSM, optical interface, electrical outputs

BATTERY POWERED ULTRASONIC WATER METERS



FLOMIC FL502x and FLOMIC FL504x

- for application in water industry
- flow-rate, volume and pressure measurement in water supply networks, detection of water leakages
- one and dual beam version, dimensions DN32 to DN200 (1 1/4" to 8")
- water pressure class MAP 16
- flow-rate sampling period 1s
- storage of measured dates
- measurement accuracy according to EN ISO 4064-1 (OIML R 49) class 2
- communication USB, RS 232, GSM, electrical outputs
- compact or remote version, protection class IP68

ULTRASONIC FLOW METERS



SONOELIS SE404x and SONOELIS SE406x

- for application in energy and light industry
- flow-rate and volume measurement electrically conductive and non-conductive liquids
- one and dual beam version, dimensions DN32 to DN300 (1 1/4" to 12")
- maximum pressure 40bar (600psi) related to diameter
- maximum temperature of measured medium 150°C (302°F)
- measurement accuracy according to EN ISO 4064-1 (OIML R 49), EN1434 (OIML R 75) class 2
- communication RS 485, electrical outputs



SONOELIS SE404x.1 and SONOELIS SE406x.1

- for application in energy, light and heavy industry
- flow-rate and volume measurement electrically conductive and non-conductive liquids
- one and dual beam version, dimensions DN32 to DN300 (1 1/4" to 12")
- maximum pressure 40bar (600psi) related to diameter
- maximum temperature of measured medium 150°C (302°F)
- measurement accuracy according to EN ISO 4064-1 (OIML R 49), EN1434 (OIML R 75) class 2
- communication RS 485, electrical outputs



SONOELIS SE401x and SONOELIS SE402x

- for application in energy and light industry
- flow-rate and volume measurement of water of big dimensions
- one and dual beam version
- dimensions DN200 to DN1200 (8" to 48")
- maximum pressure 40bar (600psi) related to diameter
- maximum temperature of measured water 150°C (302°F)
- measurement accuracy according to EN ISO 4064-1 (OIML R 49), EN 1434 (OIML R 75) class 2
- communication RS 485, electrical outputs



SONOELIS SE401x.1 and SONOELIS SE402x.1

- for application in energy, light and heavy industry
- flow-rate and volume measurement of water of big dimensions
- one and dual beam version
- dimensions DN200 to DN1200 (8" to 48")
- maximum pressure 40bar (600psi) related to diameter
- maximum temperature of measured water 150°C (302°F)
- measurement accuracy according to EN ISO 4064-1 (OIML R 49), EN 1434 (OIML R 75) class 2
- communication RS 485, electrical outputs